

# CETCO® C/S GRANULAR™

30-50 Mesh Granular Bentonite





## **DESCRIPTION**

C/S GRANULAR and CETCO CRUMBLES are granular bentonite products composed of polymer-free, dried bentonite in various mesh sizes. CETCO CRUMBLES are coarser in size than C/S GRANULAR. C/S GRANULAR and CETCO CRUMBLES are certified to NSF/ANSI Standard 60, Drinking Water Treatment Chemicals - Health Effects.

## **RECOMMENDED USE**

May be used as casing seal, hole abandonment material, and for sealing earthen structures.

#### **CHARACTERISTICS**

- Less than 10% moisture
- Provide a positive seal
- Re-hydrates
- · Will not shrink or crack

MIXING AND APPLICATION	
Grouting Material	One bag CETCO CRUMBLES to 24 gallons (91 liters) water or 24 gallons water and 8 ounces (0.25 liters) ACCU-VIS
Dry Shallow Abandonment	Pour required amount directly down borehole; hydrate with freshwater
Earthen Structure Seal	Normal treatment is 3-5 pounds per ft <sup>2</sup> (48-80 kg per m2 ) depending on soil type

# **BULK DENSITY**

65 lbs/ft3 (1.04 kg/L)

#### **PACKAGING**

50 lb (22.7 kg) bag, 48 per pallet. All pallets are plastic-wrapped.





