



OAKTON® T-100 TURBIDITY METER

Completely waterproof—even the sample chamber

Waterproof and dustproof housing – IP67-rated waterproof housing allows operation in wet conditions ensuring durability, easy cleaning, and maintenance—it even floats!

Auto-ranging from 0 to 1000 NTU – Meter determines the sample's turbidity level and automatically adjusts to the appropriate measurement range—eliminating any guesswork

Simple, display-prompted push-button calibration – Pressing the “CAL” button initiates the quick and simple calibration procedure. The instrument automatically prompts the user for the next calibration standard.

Large, easy-to read display – Large, custom LCD shows readings with units of measure and user-friendly message codes that guide meter operation

Advanced power supply management – Measures over 1200 samples with a single set of batteries, delivering quick, stable results in less than six seconds. Also features auto-off function.

Sturdy carrying case with accessories – Compact case contains all items necessary for turbidity measurements and protects the meter when not in use. Items include the T-100 meter, four primary calibration standards, three borosilicate sample cuvettes with light shield caps, collection bottle, lint-free cloth, silicone oil, and batteries.



Index markings on the cuvettes make it easy to perform repeatable measurements



Kit includes standards, sample vials, and a rugged carrying case



Drinking Water



Environmental Monitoring

Specifications

ISO9001:2000 CERTIFIED SUPPLIER CE 2 year warranty

| Model | T-100 Turbidity meter |
|------------------------------|---|
| Range | 0.1 to 19.99 NTU, 20.0 to 99.9 NTU, 100 to 1000 NTU |
| Resolution | 0.01 NTU, 0.1 NTU, 1 NTU |
| Measurement method | ISO 7027 (DIN EN 27027) compliant nephelometric method (90°) |
| Accuracy | ±2% of measurement from 0 to 500 NTU, ±3% of measurement from 501 to 1000 NTU |
| Repeatability | ±0.01 NTU or ±1% of measurement, whichever is greater |
| Response time | <6 seconds for full-step change |
| Calibration standards | 0.02 NTU, 20.0 NTU, 100 NTU, 800 NTU |

Standardization: EPA-approved polymer-based primary standards

Light source: infrared-emitting diode (850 nm wavelength)

Light source life: >1,000,000 measurements

Detector: Silicon photovoltaic

Stray light: <0.02 NTU

Display: 4-digit, 14-segment customized LCD

Sample vials: borosilicate glass with screw caps, fill line, and indexing mark. 2"H x 1"dia (51 x 25 mm)

Sample volume: 10 mL (0.33 oz) minimum

Operating temperature range: 0 to 50°C (32 to 122°F)

Operating humidity: 0 to 90% RH, noncondensing at 30°C (86°F) range

Power: four AAA alkaline batteries (included), >1200 measurements

Enclosure: ABS plastic/IP67 rated

Dimensions (W x L x H)

Meter: 2¾" x 6½" x 1⅞" (6.8 x 15.5 x 4.6 cm)

Meter with case: 6½" x 14" x 4¼" (16.5 x 35.5 x 10.5 cm)

Weight

Meter: 7 oz (200 g); **Meter with case:** 2.75 lb (1.25 kg)

Ordering Information

| Catalog number | Description | Included |
|----------------|---------------------------|--|
| WD-35635-00 | T-100 turbidity meter kit | Meter, four primary calibration standards (0.02, 20.0, 100, and 800 NTU), three empty cuvettes with light shield caps, collection bottle, lint-free cloth, silicone oil, batteries, and hard carrying case |

Accessories

WD-35635-50 Replacement calibration set, includes one 60 mL each of primary calibration standard 0.02, 20.0, 100, and 800 NTU

WD-35653-55 Replacement cuvettes, borosilicate glass. Pack of three